



Taffeta Surface

UltraGlas[®] Insights

News and Information for Architects and Designers

Taffeta

**A tactile,
durable
new
surface
with a
radiant
inner glow!**

Taffeta

A tactile new surfacing choice from the innovators at UltraGlas® — its subtle cross-linear surface texture is not as glossy as flat glass, nor as dull as frosted glass

Very versatile and durable — uses include interior and exterior tile, flooring, slabs and stair treads — including installations in freeze/thaw environments.

It's tiny angled facets refract light — providing a radiant inner glow. This effect is dramatically enhanced when used in conjunction with, or adjacent to, natural or artificial light.

Texture provides excellent coefficient of friction — for slip-resistant flooring and stair applications. An anti-slip coating is recommended for wet environments.

Available in an expansive palette of permanent, lead-free, opaque or translucent colors — opaque colorations completely obscure setting materials used in tile and flooring installations. Translucent colors are great for back-lit or other installations requiring light transmission. Colors may be specified across an entire surface or in selective areas. Most any custom color or combination of custom colors may be specified (nominal matching fee applies).

Coordinates perfectly with extensive UltraGlasTile® Line — dozens of designs, liners, decos and corners. Other glass components may be fabricated to coordinate with texture and color.

Custom physical possibilities — most shapes (including irregular shapes), sizes (up to 69-1/2" x 119-1/2") and thicknesses (up to 3/4") may be specified. Standard thickness for tile is 5/16", which coordinates well with adjacent 1/4" and 3/8" materials. Standard thickness for flooring is 3/8". Thicknesses up to 3/4" may be specified for larger format flooring, slabs and other installations requiring greater thickness. Components may be laminated to achieve necessary thickness for elevated/suspended flooring and stair tread applications. Available in all glass strengths.

Installation — very similar to ceramic tile and stone. Complete instructions packaged with all orders.

Hygienic and very low maintenance — durable surface texture conceals wear and signs of use. UltraGlas is non-porous, non-absorbent and non-abrasive.

Environmentally responsible — absolutely no lead is used in our monolithic glass colorations. Low-iron glass is used exclusively in tile manufacturing (and may be specified for all other applications). UltraGlas incorporates environmentally friendly manufacturing processes and policies.

Visit UltraGlas.com for more information, examples and inspiration. How may we help you today?



UltraGlas Inc

9200 Gazette Ave., Chatsworth CA 91311

v: 800.777.2332 f: 818.772.8231

UltraGlas.com sales@ultraglas.com